**What is claimed is:**

1.    A communicating system for relaying a communication between a server and a client, comprising:

a buffer buffering data transmitted from the server to the client and accelerating data output from the server so as to increase a throughput assigned to a connection to the client by the server; and

a transferring device transferring data stored in said buffer to the client.

2.    A communicating system for relaying a communication between a server and a client, comprising:

a receiving device receiving data transmitted from the server to the client;

a converting device converting a protocol of the received data into another protocol that allows a larger amount of data to be transferred at a time; and

a transmitting device transmitting data converted by said converting device to a network.

3. The communicating system as set forth in claim 2, further comprising:

a multiplexing device multiplexing data of multiple connections converted by said converting device,

wherein said transmitting device transmits the multiplexed data.

4. The communicating system as set forth in claim 2, further comprising:

an idling device performing an idling operation corresponding to a resource assigned to the client,

wherein said transmitting device transmits data after the idling operation is completed.

5. The communicating system as set forth in claim 2, further comprising:

a charging device performing a charging process for a service provider of the server,

wherein said receiving device receives a request from the client through the network,

wherein said charging device determines whether or not the request from the client is a request to be issued to the server,

wherein when the request from the client is the request to be issued to the server, said transmitting device transfers the request from the client to the server and said charging device

5      charges the service provider.


6.    A communicating system for relaying a communication between a serer and a client, comprising:

10      a receiving device receiving data from a network, the data obtained by converting a protocol of data transmitted from the server to the client into another protocol that allows a larger amount of data to be transferred at a time;

15      a converting device converting the protocol of the received data into the original protocol; and

a transmitting device transmitting the data converted by said converting device to the client.


20      7.    The communicating system as set forth in claim 6, further comprising:

a demultiplexing device demultiplexing data that has been multiplexed,

wherein said receiving device receives

25      multiplexed data in which data of multiple

connections has been multiplexed,

wherein said demultiplexing device demultiplexes the received data, and

wherein said converting device converts a
5   protocol of the demultiplexed data.


8.   The communicating system as set forth in claim 6, further comprising:

a charging device performing a charging
10   process for a user of the client,

wherein said receiving device receives a request to the server from the network,

wherein said charging device determines whether or not the request to the server is a
15   request from the client, and

wherein when the request to the server is the request from the client, said transmitting device transmits the request to the server and said charging device charges the user.

20

9.   A computer-readable recording medium on which a program for a computer controlling a communication between a server and a client is recorded, said program causing the computer to
25   perform:

buffering data transmitted from the server to the client and accelerating data output from the server so as to increase a throughput assigned to a connection to the client by the server; and

5      transferring the buffered data to the client.


10. A computer-readable recording medium on which a program for a computer controlling a communication between a server and a client is

10     recorded, said program causing the computer to perform:

receiving data transmitted from the server to the client;

converting a protocol of the received data

15     into another protocol that allows a larger amount of data to be transferred at a time; and

transmitting the converted data to a network.


11. A computer-readable recording medium on

20     which a program for a computer controlling a communication between a server and a client is recorded, said program causing the computer to perform:

receiving data from a network, the data

25     obtained by converting a protocol of data

transmitted from the server to the client into another protocol that allows a larger amount of data to be transferred at a time;

converting the protocol of the received data
5       into the original protocol; and

transmitting the converted data to the client.


12.  A communicating method, comprising:

forming a virtual tunnel for hiding a network
10      delay that takes place between a server and a client; and

using the virtual tunnel as a communication bypass between the server and the client so as to increase a throughput between the server and the
15      client.


13.  The communicating method as set forth in claim 12, further comprising:

charging a user of the client for a
20      communication using the virtual tunnel.


14.  The communicating method as set forth in claim 12, further comprising:

charging a service provider of the server for
25      a communication using the virtual tunnel.

15. A communicating system for relaying a communication between a server and a client, comprising:

5      buffer means for buffering data transmitted from the server to the client and accelerating data output from the server so as to increase a throughput assigned to a connection to the client by the server; and

10     transferring means for transferring data stored in said buffer means to the client.

16. A communicating system for relaying a communication between a server and a client,

15   comprising:

receiving means for receiving data transmitted from the server to the client;

converting means for converting a protocol of the received data into another protocol that allows

20   a larger amount of data to be transferred at a time; and

transmitting means for transmitting data converted by said converting means to a network.

25   17. A communicating system for relaying a

communication between a serer and a client, comprising:

receiving means for receiving data from a network, the data obtained by converting a protocol of data transmitted from the server to the client into another protocol that allows a larger amount of data to be transferred at a time;

converting means for converting the protocol of the received data into the original protocol; and

transmitting means for transmitting the data converted by said converting means to the client.

18. A propagation signal for propagating a program to a computer controlling a communication between a server and a client, said program causing the computer to perform:

buffering data transmitted from the server to the client and accelerating data output from the server so as to increase a throughput assigned to a connection to the client by the server; and

transferring the buffered data to the client.

19. A propagation signal for propagating a program to a computer controlling a communication

between a server and a client, said program causing the computer to perform:

receiving data transmitted from the server to the client;

5      converting a protocol of the received data into another protocol that allows a larger amount of data to be transferred at a time; and

transmitting the converted data to a network.

10      20. A propagation signal for propagating a program to a computer controlling a communication between a server and a client, said program causing the computer to perform:

receiving data from a network, the data

15      obtained by converting a protocol of data transmitted from the server to the client into another protocol that allows a. larger amount of data to be transferred at a time;

converting the protocol of the received data

20      into the original protocol; and

transmitting the converted data to the client.